قیمت محصولات Akuvox | نیمه اول 2026

	Product Image	Product Name	Description	Price
Door Phone		**Akuvox S539** **Smart Intercom** **& installation kit**	Industry-first Metaverse Android Door Phone 1.Size: 367.5x183x35.5mm 2.Front Panel: Aluminum 3.Display: 10 Inch IPS LCD 4.Main Camera: 5M pixels, with starlight 5.Light Sensor: Support 6.Motion Sensor: Support 7.ToF Sensor: Support 8.Wiegand Port: Support 9.RS485 Port: Support 10.Line Out: Support 11.RF Card Reader: 13.56MHz & 125kHz 12.Relays Out: 3 13.Inputs: 3 14.Reset Button: 1 15.IP & IK Level: IP66 & IK08 16.Onvife	**2464$**
		Akuvox **S535** **Smart Intercom &** **installation kit**	Sinch Facial Recognition Door Phone 1. H.264 video and G.722 audio codec 2. Display: 5" IPS LCD capacitive touch screen 1280x720 4. Camera: 2 Mega pixels, WDR 5. Protection Level: IP66/IK08 6. PoE+ (IEEE802.3at, Power-over-Ethernet) 7.Support Wiegand, RS485, 13.56MHZ&125KHZ Card reader 8.Complies with SIP standard for easy integration in every SIP PBX 9. Installation: support Surface Mount and Flush Mount by using different bracket or box	**896$**
		Akuvox **S535** **Smart Intercom &** **installation kit**	Sinch Facial Recognition Door Phone 1. H.264 video and G.722 audio codec 2. Display: 5" IPS LCD capacitive touch screen 1280x720 4. Camera: 2 Mega pixels, WDR 5. Protection Level: IP66/IK08 6. PoE+ (IEEE802.3at, Power-over-Ethernet) 7.Support Wiegand, RS485, 13.56MHZ&125KHZ Card reader 8.Complies with SIP standard for easy integration in every SIP PBX 9. Installation: support Surface Mount and Flush Mount by using different bracket or box	**1221$**
		Akuvox X915 **Smart Intercom &** **installation kit**	High-end Smart Door Phone 1.Size: 350x130x53.9mm (HxWxD) 2.Body material: 316 grade stainless steel 3.RAM / ROM: 2GB / 16GB 4.Display: 8" IPS LCD 5.Screen: 8" capacitive touch screen 6.Camera: 2MP camera,star light 7.Relay In/Out: 3/3 8.Card reader: 13.56MHz & 125kHz 9.RS485 & Weigand port 10.IR Sensor 11.Installation: In-wall 12.Water-proof & Dust-proof: IP65 13. IK10 14. Onvif	**2464$**
		Akuvox **X912** **Smart Intercom** **+** **installation kit**	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Weigand port 8.linux 9.Installation: in wall 10.Water-proof & Dust-proof:IP65 11.IK10	**1456$** **+** **90$**
		Akuvox X912K **Smart Intercom** **+** **installation kit**	Vandal-resistant Door Phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Weigand port 8.linux 9.Installation: in wall 10.Water-proof & Dust-proof:IP65 11.IK08 12.Numeric keypad with extra buttons	**1120$** **+** **90$**

		Akuvox R29CL **Smart Intercom &** **installation kit**	SIP Android Door Phone with Facial LTE module 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	**2106$**
		Akuvox R29CB smart intercom & **installation kit**	SIP Android Door Phone with Facial Recognition&mask&temperture muserment 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	**3080$**
		Akuvox R29CT **smart intercom &** **installation kit**	SIP Android Door Phone with Facial Recognition&FingerPriting 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	**2024$**
		Akuvox R29C **Smart Intercom &** **installation kit**	SIP Android Door Phone with Facial Auxiliary Camera 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	**1848$**
		Akuvox R29S **Smart Intercom &** **installation kit**	SIP Android Door Phone with Facial Standard version 1.Size: 324x130x27mm (HxWxD) 2.Body material: Aluminum 3.RAM / ROM: 2GB / 16GB 4.Display: 7" IPS LCD 5.Screen: 7" capacitive touch screen 6.Camera: 3MP camera, automatic lighting; a 7.second 5MP camera (For R29C only) - BIO Detection 8.Relay In/Out: 3/3 9.Card reader: 13.56MHz & 125kHz 10.RS485 & Weigand port 11.IR Sensor 12.Installation: In-wall 13.Water-proof & Dust-proof: IP65 14.POE or 12V DC Connector (if not using PoE)	**1496$**
		Akuvox E16 **Smart Intercom** **+** **installation kit**	budget-friendly face recognition door phone 1.Linux 2. Display: 5 Inch IPS LCD, 1280x720 3. Camera: 2M pixels, WDR 4.Wiegand & RS485 Port: Support 5.RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8. 802.3af Power-over-Ethernet 9. POE Or 12V DC Connector (if not using PoE) 10.Tamper: Support 11 Installation: Wall-mounted 12. Water-proof & Dust-proof:IP65 13. NFC & Blutooth	**700$** **+** **90$**
		Akuvox E18 **Smart Intercom** **+** **installation kit**	budget-friendly face recognition door phone 1.Linux 2.Housing Material: Plastic 3.Display: 7 Inch IPS LCD, 1024x600 4.Camera: 2M pixels, WDR 5.Wiegand & RS485 Port: Support 6.Relay In / Out: 3 / 2 7.Bluetooth: Support 8.POE Or 12V DC Connector (if not using PoE) 9.Tamper: Support 10.Installation: Wall-mounted 11.Water-proof & Dust-proof:IP65 12.RF Card Reader: 13.56MHz,125kHz & NFC 13.Linux	**902$** **+** **90$**

		Akuvox R28A IP Video Intercom	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 4.3 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand &.RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	**846$**
		Akuvox S532 ST & installation kit	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 2.8 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand &.RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall 12.IK08 & IP66 13.RFID/NFC/Bluetooth	**739$**
		Akuvox S532 IP VERSION & installation kit	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Display: 2.8 Inch, color TFT LCD 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand &.RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall 12.IK08 & IP66 13.RFID/NFC/Bluetooth	**706$**
		Akuvox R27A IP Video Intercom	SIP Intercom with Keypad 1.front panel material: Aluminium 2.Output Relay: 3 output relays for door opener 3.Camera: 2M pixels, automatic lighting 4.Wide-angle camera: 116° (H), 60° (V) 5.Numeric keypad with extra buttons 6.Infrared Sensor: Support 7.Wiegand &.RS485 port: Support 8.POE or 12V DC Connector (if not using PoE) 9. Card reader: 13.56MHz & 125kHz 10.Complies with SIP standard for easy integration in every SIP PBX 11.Installation: In-wall	
		Akuvox R20K + installation kit	Palm-size Door phone 1.Front panel：Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120º 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand &.RS485 port: Support 12.Card reader: 13.56MHz & 125kHz	**431$ + 37$**
		Akuvox R20K - Black + installation kit	Palm-size Door phone 1.Front panel：Aluminum alloy 2.Output Relay: 2 output relays for door opener 3.Water-proof & Dust-proof: IP65 4.Wide-angle camera: 120º 5.POE Or 12V DC Connector (if not using PoE) 6.DIM: 226x108x52mm 7.Complies with SIP standard for easy integration in every SIP PBX 8. Installation: on-wall 9.Linux 10.Onvif 11.Wiegand &.RS485 port: Support 12.Card reader: 13.56MHz & 125kHz	**431$ + 37$**
		Akuvox R20B5X + installation kit	1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 5 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Flush-mounted DIM: 226x108x52mm 18. Onvif	**394$ + 37$**

		Akuvox R20B4X **+** **installation kit**	Multi-botton Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 4 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	**382$** **+** **37$**
		Akuvox R20B3X **+** **installation kit**	Multi-botton Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 3 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation:in-wall 17. Onvif	**370$** **+** **37$**
		Akuvox R20B2X **+** **installation kit**	Multi-botton Door Phone for limited space 1. Front panel: Aluminum alloy 2. Camera: 2M pixels, automatic lighting 3. Buttons: 2 4. Light sensor: Support 5. Infrared sensor: Support 6. Wiegand & RS485 port: Support 7.Linux 8. RF card reader: 13.56MHz & 125kHz 9. Relays out: 2 10. Inputs: 2 11. Microphone: -40dB Speaker: 4Ω / 2W 12. Ethernet port: RJ45, 10/100Mbps adaptive 13. 802.3af Power-over-Ethernet 14. POE or 12V DC Connector (if not using PoE) 15. Water-proof & Dust-proof: IP65 16. Installation: in-wall 17. Onvif	**345$** **+** **37$**
		Akuvox x910	1. Front panel: Aluminum 2. Single speed-dial button with blue backlight; 3. Wide-angle of main camera: 150º (H), 116º (V), 5M pixels 4. Auxiliary Camera: 2M pixels, automatic lighting 5. Package Detection & QR Code Scanning 6. Complies with SIP & ONVIF 7. IK08& IP66	**840$**
		Akuvox R20A **+** **installation kit**	single-button SIP video door phone 1.Linux 2.Body material: Aluminum 3.Camera: 3M pixels, automatic lighting,Wide-angle camera: 116º 4.RF Card Reader 13.56MHZ&125KHZ Card reader 5.Output Relay: 2 output relays for door opener 6.Water-proof & Dust-proof: IP65 7.Installation:On-wall 8.POE or 12V DC Connector (if not using PoE) 9.Wiegand & RS485 port:Support 10.Complies with SIP standard for easy integration in every SIP PBX; 11. Onvif	**299$** **+** **37$**
		Akuvox R20A-2-wire **+** **installation kit**	Linux single-button SIP video door phone 1.Body material: Alluminum 2.Camera: 2M pixels, automatic lighting,Wide-angle camera: 120º3.RF Card Reader 13.56MHZ&125KHZ Card reader 4.Output Relay: 1 output relays for door opener 5.Water-proof & Dust-proof: IP65 6.Installation: on-wall 7.Onvif 8.Power supply：48VDC two-wire power supply 9.Complies with SIP standard for easy integration in every SIP PBX;	**366$** **+** **37$**
		Akuvox R25A **+** **installation kit**	Linux Single speed-dial button with blue backlight 1.Body material: Alluminum 2.Camera:4M pixels, automatic lighting 3.RF card reader: 13.56MHz & 125kHz, NFC 4. Relays out: 2 5. IP Rating: IP65 6. Installation: Flush-mounted or Wall-mounted 7.Onvif 8. 802.3af Power-over-Ethernet 9.Wide-angle camera: 150º (H), 150º (V)	**366$** **+** **37$**
		Akuvox E13S & **installation kit**	Linux single-button SIP video door phone 1.Size:234x94x34mm 2.front panel: Stainless steel 3.Display: 4 Inch, color TFT LCD, touchable 4.Camera: 2M pixels 5.Relays out: 2 6.RF card reader: 13.56MHz & 125kHz, NFC 7.RS485 & Weigand port 8.POE or 12V DC Connector (if not using PoE) 8.POE or 12V 9.Installation: in wall-on wall 10.Water-proof & Dust-proof: IP65	**179$**

		Akuvox SIP Intercom-E12W	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95º angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth and WIFI 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65	**193$**
		Akuvox E12S SIP Intercom	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95º angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz,NFC,Bluetooth 7.micro SD Card Slot: 1 8.Onvif 9.Wiegand & RS485 port:Support 10. Water-proof & Dust-proof: IP65	**174$**
		Akuvox DB01 SIP Intercom	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95º angle , LED White Light 3.Output Relay: 1 output relays for door opener 4.Installation: on-wall 5.: 1 call buttonInfrared 6.Onvif 7.Wiegand & RS485 port:Support 8. Water-proof & Dust-proof: IP65 9.power supply: 12v 2A	**129$**
		Akuvox E11 SIP Intercom + Installation Kit	Linux single-button SIP video door phone 1.Body material: ABS plastics 2.Camera: 2M pixels with 95º angle , LED White Light 3.Output Relay: 2 output relays for door opener 4.Installation: on-wall 5.Infrared sensor 6.: 1 call buttonInfrared Sensor: SupportRF card reader: 13.56 MHz and 125 kHz 7.Onvif 8.Wiegand & RS485 port:Support	**228$ + 37$**
		Akuvox E20S SIP Intercom	Linux single-button SIP intercom 1.Body material: Aluminium 2.Output Relay: 2 output relays for door opener 3.Installation: on-wall 4.Infrared sensor 5.1 call button,Infrared Sensor 6.Wiegand & RS485 port:Support	**280$**
indoor monito		**Akuvox x937 SIP touch Panel**	Smart AI Monitor 1. 15.4" touch screen with 1920 x 1080 resolution 2. Android 14 3. Support Ethernet & WiFi6 4. Powered by PoE+ or external source 5. Support HDMI input and CCTV system integration 6. Built-in AI voice assistant 7. On-wall or desktop mounting options available	**1344$**
		Akuvox S567W SIP touch Panel	A smart intercom, as well as a gear for audiophile 1.1280*800 2.Android 12 3.Front panel: Plastic 4.RAM / ROM: 4GB /16 GB 5.Display: 10 Inch IPS LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 2 9.Bell in: 1 10.Alarm Input：8 11. Wifi 12.Bluetooth	**661$**
		Akuvox S567 SIP touch Panel	A smart intercom, as well as a gear for audiophile 1.1280*800 2.Android 12 3.Front panel: Plastic 4.RAM / ROM: 2GB /8 GB 5.Display: 10 Inch IPS LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 2 9.Bell in: 1 10.Alarm Input：8	**627$**
		Akuvox S565 SIP touch Panel	1.resolurion 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 10 Inch TFT LCD 6.Screen: 10 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell in: 1 10.Alarm Input：8	**358$**
		Akuvox S563W SIP touch Panel	Android SIP Indoor 1.8" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6.WIFI Enabled , Blutooth 7.front panel: plastic 8.RS485 port: Support 9.Relays out: 1 10.IO:8 11.Android 12	**366$**

		Akuvox S563 **SIP touch Panel**	Android SIP Indoor 1. 8" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6.front panel: plastic 7.RS485 port: Support 8.Relays out: 1 9.IO:8 10.Android 12	**333$**
		Akuvox S562W **SIP touch Panel**	1.resolurion 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 7 Inch TFT LCD 6.Screen: 7 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell in: 1 10.Alarm Input：8 11.Wifi & blutooth	**215$**
		Akuvox S562 **SIP touch Panel**	1.resolurion 1024*600 2.Linux 3.Front panel: Plastic 4.RAM / ROM: 128MB /128MB 5.Display: 7 Inch TFT LCD 6.Screen: 7 Inch capacitive touch screen 7.RS485 Port: Support 8.Relays Out: 1 9.Bell in: 1 10.Alarm Input：8	**181$**
		Akuvox IT88A **SIP touch Panel**	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: Aluminium alloy 3.Bluetooth,wifi, Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. .Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE port: 1 Port	**728$**
		Akuvox IT88S **SIP touch Panel**	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: Aluminium allo. 3.Powered by PoE or external source 4.Supports US or European electrical wall box mounting 5. .Reception of a HD picture from the door communicator 6. IO: 8 7.Two-way communication based on SIP v2.0 protocol 8.RS485 port: Support 9.Relays out: 2 10.Installation: Wall-mounted & Desktop 11.POE or 12V DC Connector (if not using PoE) 12. PoE port: 1 Port	**728$** **+** **90$**
		Akuvox C319A **SIP touch Panel (SIP SERVER Enabled)**	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3.Bluetooth,wifi, Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. .Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE Port: 1 port	**616$**
		Akuvox C319W **SIP touch Panel (SIP SERVER Enabled)**	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3.Bluetooth,wifi 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. .Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE Port: 1 port	**582$**
		Akuvox SIP touch Panel-C319S (SIP SERVER Enabled)	SIP Indoor unit (Android Version 9) 1.10" capacitive touch screen with energy saving mode 2. body material: plastic 3. Camera 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. .Reception of a HD picture from the door communicator 7. IO: 8 8.Two-way communication based on SIP v2.0 protocol 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE) 13. PoE Port: 1 port	**549$**

		Akuvox SIP Touch Panel X933W	SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. Bluetooth,wifi 7. body material: plastic 8.IO: 8 9.RS485 port: Support 10.Relays out: 2 11.Installation: Wall-mounted & Desktop 12.POE or 12V DC Connector (if not using PoE)	**493$**
		Akuvox X933W **SIP Touch Panel In-wall**	SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. Bluetooth,wifi 7. body material: plastic 8.IO: 8 9.RS485 port: Support 10.Relays out: 2 11.POE or 12V DC Connector (if not using PoE)	**493$**
		Akuvox X933S **SIP Touch Panel &** **Installation kit**	SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. body material: plastic 7.RS485 port: Support 8.Relays out: 2 9.Installation: Wall-mounted & Desktop 10.IO:8	**457$**
		Akuvox X933S **SIP Touch Panel In-wall** **& Installation kit**	SIP Indoor unit (Android Version 9) 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6. body material: plastic 7.RS485 port: Support 8.Relays out: 2 9.IO:8	**569$**
		Akuvox C316W **SIP touch Panel**	Front panel: Plastic OS ： Android 12 RAM / ROM: 2GB / 8GB Display: 7 Inch TFT LCD Screen: 7 Inch capacitive touch screen RS485 port: Support Relay out: 1 Bell in: 1 I/O: 8 Microphone: -58dB Speaker: 4Ω / 2W Ethernet ports: 2xRJ45, 10/100Mbps adaptive 802.3af Power-over-Ethernet 12V DC connector (if not using PoE) Installation: Wall-mounted & Desktop Dimension: 200.2x132.2x27.2mm Working Humidity: 10~90% Working Temperature: -10°C ~ +45°C Storage Temperature: -20°C ~ +70°C	**333$**
		Akuvox C313w **SIP touch Panel 2wire**	Linux SIP Indoor 1.2-wire ports: 2 pair 2.7" capacitive touch screen with energy saving mode 3.Reception of a HD picture from the door communicator 4.Two-way communication based on SIP v2.0 protocol 5.48V DC connector (if not using NS-2) 6.Supports US or European electrical wall box mounting 7.front panel: plastic 8.RS485 port: Support 9.Relays out: 1 10.IO:8 11. Installation: Wall-mounted & Desktop	**222$**
		Akuvox C313S **SIP touch Panel**	Linux SIP Indoor 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.POE or 12V DC Connector (if not using PoE) 5.Supports US or European electrical wall box mounting 6.front panel: plastic 7.RS485 port: Support 8.Relays out: 1 9.IO:8 10. Installation: Wall-mounted & Desktop	**160$**
		Akuvox C313N **SIP touch Panel**	Linux SIP Indoor 1.7" capacitive touch screen with energy saving mode 2.Reception of a HD picture from the door communicator 3.Two-way communication based on SIP v2.0 protocol 4.Powered by PoE or external source 5.Supports US or European electrical wall box mounting 6. with one LAN port 7. I/O port not available 8. not Relay 9.front panel: plastic 10.Installation: Wall-mounted & Desktop	**148$**
		Akuvox S560	1. Wifi 2. HD audio 3. Ethernet Port: RJ45, 10/100Mbps adaptive 4.POE or 12V DC Connector (if not using PoE) 5. Installation: Wall-mounted 6.Working Humidity: 10~90%, no condensing 7. Working Temperature: -10℃~+45℃	**78$**

IP Phone		**VP-R49G**	SIP based Android Video phone 1. 7" touch screen with 1024 x 600 resolution 2. Android 9.0 OS 3. Premium audio and video quality 4. DTMF for remote door opening 5. Camera:2MP with privacy shutter 6. Built-in Bluetooth, USB, and Wi-Fi 7. Support 3rd-party apps 8. Support 2 Sip Accont 9. RJ9 Handset 10. POE 11.Support Call Waiting, Call Forward, Call Transfer 12. Call on Hold, Mute, Auto-answer, Redial, DND 13.Local 3-Way Conference	**616$**
		SP-R50P	HD Voice 2.3" 132*64 Graphical LCD with Backlight Support 3-way Conference Support PoE Fully Compatible with Asterisk, BroadSoft Platform Dimensions mm: 209 x199 x 104 Weight g: 800 Voltage: 100 ~ 240 V AC	**112$**
Access Control		**Akuvox A01**	IP-based access control terminal that combines door controller and card reader in one device. 1.card reader:125kHZ and 13.5MHZ RFID card and NFC 2.Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4.Wiegand 5. Tamper-proof Sensor 6. Relay out:1 7.TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9.Capacity:up to 10,000 card and 100,000 event logs 10.Water-proof & Dust-proof: IP65 11.Installation: on-wall or in-wall	**207$**
		Akuvox A02	IP-based access control terminal that combines door controller and card reader in one device. 1.card reader:125kHZ and 13.5MHZ RFID card and NFC 2.Aluminum frame, front panel Toughened Glass 3. Dimension: 86 x 86 x 33 (mm) 4.Wiegand 5. Tamper-proof Sensor 6. Relay out:1 7.TCP/IP Communication 8. POE or 12V DC connector (if not using PoE) 9.Capacity:up to 20,000 card and 100,000 event logs 10.Water-proof & Dust-proof: IP65 11.Installation: on-wall or in-wall	**246$**
		Akuvox A03	IP-based access control terminal combining a reader and a door controller. It offers flexible credentials, including wave-to-unlock via Bluetooth, mobile access via NFC, and RFID cards. 1.Front panel: Toughened Glass 2.Aluminum frame, front panel Toughened Glass 3.RFID card reader: 13.56MHz & 125kHz 4.Bluetooth:BLE5.0 5.Relay out: 1 6.Inputs: 2 7.Wiegand: Support 8.Power output: 12V 600mA 9.Water-proof & Dust-proof: IP65 10.Installation: on-wall or in-wall 11.Dimension: 86 x 86 x 33 (mm) 12.Capacity:up to 20,000 card and 100,000 event logs 13. POE or 12V DC connector (if not using PoE) 14.Water-proof & Dust-proof: IP65	**298$**
		Akuvox A092	intelligent access controller housed in a stylish SGCC cabinet 1.Front panel: SGCC 2. Support up to 50,000 cards and 100,000 event logs 3. Support RS485,OSDP, and Wiegand Protocols 4. Temper-proof Sensor 5. Backlit Function icons 6. Suppurt backup buttery 7.Wiegand port: 4 8. Relays out: 2 9.Exit button input: 2 10.Installation: Wall-mounted 11. Dimension: 365 x 340 x 86 (mm) 12.POE or 12V 800mA per door for locks/strikes, readers, and input devices 13.Backup battery: Support	**672$**
		Akuvox A05S **+** **Installation kit**	smart access control device with facial recognition 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3.Wiegand & RS485 Port: Support 4.NFC 5.RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8.Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11 Installation: Wall-mounted 12.Water-proof & Dust-proof: IP65 13.Working Humidity: 10~90%, no condensing 14. Working Temperature: -20℃~+60℃	**388$** **+** **90$**

		Akuvox Module MD01	smart access control device with facial recognition wrist temperature measurement 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3.Wiegand & RS485 Port: Support 4.NFC 5.RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8.Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11 Installation: Wall-mounted 12.Water-proof & Dust-proof: IP65 13.Working Humidity: 10~90%, no condensing 14. Working Temperature: -20℃~+60℃ 15.20,000 face capacity & 20,000 card capacity	**190$**
		Akuvox Module MD02	smart access control device with facial recognition with forahead temperature measuremen 1. 5" screen with energy saving mode, 1280x720 2. Camera: 2M pixels, WDR 3.Wiegand & RS485 Port: Support 4. NFC 5.RF Card Reader: 13.56MHz 6. Relay In / Out: 1 / 1 7. Ethernet Port: RJ45, 10/100Mbps adaptive 8.Housing Material: Plastic 9. POE or 12V DC Connector (if not using PoE) 10. Tamper: Support 11 Installation: Wall-mounted 12.Water-proof & Dust-proof: IP65 13.Working Humidity: 10~90%, no condensing 14. Working Temperature: -20℃~+60℃ 15.20,000 face capacity & 20,000 card capacity	**672$**
		A08K	Front panel: Toughened Glass Frame: Aluminum Alloy RFID card reader: 13.56MHz & 125kHz Relay out: 1 Inputs: 2 Wiegand: Support RS485: Support Speaker: 8Ω / 0.5W Tamper proof alarm: Support Ethernet port: RJ45, 10/100Mbps adaptive 12V DC connector (if not using PoE) Power output: 12V 600mA IP Level: IP65 IK Rating: IK09 Installation: Flush-mounted or Wall-mounted Dimension: 50 x 140 x 26.7 (mm) Working Humidity: 10~90%, no condensing Working Temperature: -20°C ~ +55°C Storage Temperature: -30°C ~ +70°C	**336$**
		A08S	Front panel: Toughened Glass Frame: Aluminum Alloy RFID card reader: 13.56MHz & 125kHz Relay out: 1 Inputs: 2 Wiegand: Support RS485: Support Speaker: 8Ω / 0.5W Tamper proof alarm: Support Ethernet port: RJ45, 10/100Mbps adaptive 12V DC connector (if not using PoE) Power output: 12V 600mA IP Level: IP65 IK Rating: IK09 Installation: Flush-mounted or Wall-mounted Dimension: 50 x 140 x 26.7 (mm) Working Humidity: 10~90%, no condensing Working Temperature: -20°C ~ +55°C Storage Temperature: -30°C ~ +70°C including PIN code, QR scanning, wave-to-unlock via Bluetooth, mobile access via NFC and RFID cards.	**392$**
		Akuvox NS-2	2-Wire IP network switch 1.Support network and power supply for R20A-2 or C313W-2 through 2-wire cable; 2.Support multi-level cascade through 2-wire cable; 3.Connects up to 6 pcs of Akuvox 2-wire IP intercom devices; 4.Super long transmission distance via 2-wire cable; 5.Powerd by 48VDC or 24VDC power supply unit; 6.Rail mounting installation; 7.2-wire ports: 6 8.Status Indicator: 4 9.RJ45 port: 1	**235$**
		Akuvox EC-32	1.High performance 32bit CPU processor 2.Standard 10/100M TCP/IP communication 3.Big capacity flash chip, 120,000 card holders and 200,000 records 4.Each panel support 32 outputs and can connect a 5.expansion panel to reach 64 outputs 6.One RS485 port for connecting expansion panel 7.Supports emergency door release input to realize fire alarm linkage or elevator's normal usage if emergency 8.Supports 1 Wiegand reader with Wiegand 26/34 protocol 9.Support working with Akuvox intercom devices by HTTP mode	**818$**